

# Z+F IMAGER® 5010 C

The Z+F IMAGER® 5010C is a compact high-speed phase-based laser scanner with integrated HDR-camera, great precision, range and spherical field of view. The unique stand-alone concept with integrated battery and color display with touch screen, as well as a digital dynamic compensator and a laser plummet enable very flexible use in real environments.

Laser system			
Laser class	1		
Beam divergence	< 0.3 mrad		
Beam diameter	approx. 3.5 mm @0,1 m		
Range	187.3 m (unambiguity interval)		
Minimum distance	0.3 m		
Resolution range	0.1 mm		
Data acquisition rate	Max. 1.016 million pixel/sec.		
Linearity error <sup>1</sup>	≤ 1 mm		
Range noise	black 14 %	grey 37 %	white 80 %
Range noise, 10 m <sup>12</sup>	0.4 mm rms	0.3 mm rms	0.2 mm rms
Range noise, 25 m <sup>12</sup>	0.6mm rms	0.4 mm rms	0.3 mm rms
Range noise, 50 m <sup>12</sup>	2.2 mm rms	0.8 mm rms	0.5 mm rms
Range noise, 100 m <sup>12 3</sup>	10 mm rms	3.3 mm rms	1.6 mm rms
Temperature drift	negligible		

Deflection unit	
Vertical system	completely encapsulated rotating mirror
Horizontal system	device rotates about its vertical axis
Vertical field of view	320°
Horizontal field of view	360°
Vertical resolution	0.0004°
Horizontal resolution	0.0002°
Vertical accuracy <sup>1</sup>	0.007° rms
Horizontal accuracy <sup>1</sup>	0.007° rms
Rotation speed	max. 50 rps (3,000rpm)

Deflection unit		Scan duration			
Angle resolution	pixel/360° horizontal & vertical	less quality <sup>6</sup>	normal quality <sup>6</sup>	high quality <sup>6</sup>	premium quality <sup>6</sup>
“preview“ <sup>4</sup>	1,250	---	0:26 min	---	---
“low“	2,500	0:26 min	0:52 min	1:44 min	---
“middle“	5,000	0:52 min	1:44 min	3:22 min	6:44 min
“high“	10,000	1:44 min	3:22 min	6:44 min	13:28 min
“super high“	20,000	3:28 min	6:44 min	13:28 min	26:56 min
“ultra high“ <sup>5</sup>	40,000	---	13:28 min	26:56 min	53:20 min
“extremely high“ <sup>5</sup>	100,000	---	81:00 min	162:00min	---

1. Detailed explanation on request – please contact [info@zf-laser.com](mailto:info@zf-laser.com)
2. Data rate 127,000 pixel/sec (equivalent to “High Resolution / high quality” setting), 1 Sigma range noise, unfiltered raw data
3. Not tested during production
4. Not intended for surveying purposes! To be used only for preview / selection scan definition.
5. Huge amounts of data will be generated! Recommended for high resolution, small area selection scans only.
6. Choosing the next higher quality setting will double scanning time and reduce range noise by a factor of 1.4.

# Z+F IMAGER® 5010 C

Miscellaneous		
Dynamic Compensator	resolution: 0.001° measurement range: +/- 0.5° accuracy: < 0.007° selectable on/off	The Dynamic Compensator will correct angular tilt for each pixel during scan acquisition.
Laser plummet	laser class: 2 accuracy of plummet: 0.5 mm/1m laser point diameter: < 1.5 mm at 1.5 m	
Levelling display	electronic level in onboard display and Z+F LaserControl® Scout	
Data storage	internal 64 GB flash card, 2 x 32 GB USB external flash drive	
Data transmission	Ethernet or USB 2.0	
Integrated control panel	touch screen with 5.7" colour display	
Interfaces	2 x USB, LEMO 9-pin und LEMO 7-pin connections for external sensors (GPS, odometer, etc.)	

Power supply	
Input voltage	24 V DC (scanner) ; 100 – 240 V AC (power unit)
Power consumption	< 65 W (on average)
Operating time	> 3 h (internal battery)

Ambient conditions	
Operating temperature	-10 °C ... +45 °C
Lighting conditions	operational in all conditions
Humidity	non-condensing
Protection class	IP 53

Dimensions and weights	
Scanner	
Dimensions (w x d x h)	170 x 286 x 395 mm
Weight	9.8 kg
Battery	
Dimensions (w x d x h)	170 x 88 x 61 mm
Weight	1.2 kg
AC power unit	
Dimensions	35 x 67 x 167 mm
Weight	0.54 kg

HDR camera	
focus area	1m - ∞
panorama compilation	
image count for panorama	42
recording time (depends on light conditions)	ca. 3:30 min.
panorama resolution	ca. 80 MPixel